



33LK

Low Profile Luminaire

Stainless steel, brass, aluminum.
31 -42" adjustable height 787 -1067mm.
LK shield rotates 360° horizontally on dual vertical pivot control tube.
Stem with dome base rotates 700° between stops.

Adjustable stance feet:
Retractable geared feet move in or out to support very small (5" diam) base on hard floors to medium pile carpet. Inquire for deep pile/shag conditions. Special strategies may be available.

36 volt DC LED Shield:
Holds 48 high brightness 3500K Nichia LEDs.
A magnetic low brightness louver prevents glare.
A programmed microprocessor provides thermal regulation and wide range PWM dimming.

*36 Volt DC Power

*The included international power supply delivers 36v DC from standard US 110-125 VAC as well as International voltages from 90 to 240 VAC.

*Cord from power source to Power Supply.

*125 VAC Cord: 6' Black (UL)SVT 75°C.

*Cord from Power Supply to Luminaire:

* 36v DC Cord: 9' slender red or linen colored braid.

Uses less than 20w for diffuse task light.
Eliminates incandescent 75-100w heat issues.
The ultimate green lighting device.
Cool!

©Cedric Hartman 2010
All rights reserved



33 LK

Adjustable stance feet
retracted for hard floor
installation

© Cedric Hartman 2010
All rights reserved